

SAMURAI SERIES

- ★ **WARRANTY** / Limited lifetime
- 🔗 **CABLE** / Wire or Synthetic
- ⚡ **POWER TYPE** / Electric 12v/24v
- 🏋️ **PULLING POWER** / 3 628 - 6 577 kg



Wireless 2.4G Remote Control
(12v Models Only)



3.8m Remote Handset



Isolation Switch



Heavy Duty Battery Leads



Stainless Steel Mounting hardware

Ideal for recovery and 4x4 applications. Outstanding features include high quality series wound double sealed motor with solid brass contacts, heavy duty 4 pin waterproof contactors, double sealed drum on maintenance free bearings and quiet, efficient full steel planetary gearing. Comes with stainless steel roller fairlead and fittings as standard.

- Revolutionary Design External Brake
- 600 amp Silver Tip Contactor
- Silver Copper Motor with Copper Brush Holders
- Extensive Waterproof Sealing to IP68 Standard
- HRC50 Full Steel Gears

Model	Line Pull	Motor	Gearing	Drum (DxL)	Cable (dia. x L)	Size	Weight
800VS12/24 800VA12	8000 lbs (3636 kg)	12v: 5.8hp 4.3kW 24v: 7.4hp 5.5kW	196:1	63 x 223 mm	8.3mm x 29m (W) 8mm x 25m (S)	559 x 160 x 248mm	39 kg (W) 28 kg (S)
950VS12/24 950VA12	9500 lbs (4500 kg)	12v: 6.1hp 4.6kW 24v: 7.6hp 5.7kW	196:1	63 x 223 mm	9.2mm x 26m (W) 9.5mm x 25m (S)	559 x 160 x 248mm	40 kg (W) 30 kg (S)
95DVA12 (Short Drum)	9500 lbs (4500 kg)	12v: 6.1hp 4.6kW 24v: 7.6hp 5.7kW	196:1	63 x 120 mm	9.2mm x 14m (W) 9.5mm x 15m (S)	456 x 160 x 248mm	32 kg (W) 27 kg (S)
120VS12/24 120VA12/24	12000 lbs (5400 kg)	12v: 6.7hp 5.0kW 24v: 8.0hp 6.0kW	253:1	63 x 223 mm	10.2mm x 25.5m (W) 11mm x 25m (S)	559 x 160 x 248mm	44 kg (W) 32 kg (S)
145VS12 145VA12/24	14500 lbs (6577 kg)	12v: 7.2hp 5.4kW 24v: 8.3hp 6.2kW	253:1	63 x 223 mm	10.2mm x 25.5m (W) 11mm x 25m (S)	593 x 160 x 248mm	43 kg (W) 33 kg (S)